



SRM INDUSTRIES INC.




The Toughest Hose Protection Products on the Planet...Period!

RHINO WRAP™ RXX

RHINO WRAP EXTRA TOUGH THE ULTIMATE ABRASION RESISTANT SLEEVE

RHINO WRAP™ RXX is a heavy-duty product with a unique, high lubricity coating with similar wear characteristic to "tough cover" hose products. **RHINO WRAP™ RXX** is constructed using Military Spec 1500 denier woven hybrid fabric with an 83-durometer coating. This results in a product which offers the best abrasion wrap choice available today.



(Oil Rig application in West Texas)


Features & Benefits:

RHINO WRAP™ RXX has nearly twice the mass and four to six times the abrasion resistance of our other **RHINO WRAP** products. **RHINO WRAP™ RXX** has the most enhanced wear reinforcement areas for extreme duty requirements.

Hoses in static positions also benefit from using **RHINO WRAP™ RXX** to minimize vibration due to pumping flow, abrasion from moving hoses, and hose damage from cover contact. **RHINO WRAP™ RXX** can prevent accidental damage and protect operators from unshielded hose failure.

RHINO WRAP™ RXX is reusable and features Mil-Spec Heavy-Duty hook and loop closures, which allows for installation without disconnecting hoses and can reduce labor time by 70%.

Testing on the **RHINO WRAP™ RXX** (see picture below) is an example from a drag test performed in a subsea application.



The most challenging part of the job comes from dragging the heavy 600 ft. bundle, (which equals 40psi ground pressure) over rough concrete, on to the dock, during inspection and storage preparation. With the force and weights involved in oil and gas industry applications, along with the extremely high cost of down time, **RHINO WRAP™ RXX** is the recommended product for you to spec in for your extreme applications.

Manufactured in the USA for SRM Industries Inc.





SRM INDUSTRIES INC.



The Toughest Hose Protection Products on the Planet...Period!

RHINO WRAP™ RXX

RHINO WRAP EXTRA TOUGH THE ULTIMATE ABRASION RESISTANT SLEEVE

Designed to handle extreme applications.

Some applications for RXX are:

- Oil Field Industry
 - Frac Hoses
 - Rotary Hoses
 - Drill Rigs
 - Dock Hoses
- Forestry Industry



Tested 5 times tougher than any other sleeve

- Material:** Proprietary Engineered fabric
- Temperature Range:** -60° F to 250° F; (-51°C to +121°C)
- Abrasion:** Excellent; Meets ISO 6945 Specifications
- Puncture / Tear:** Excellent; very puncture and tear resistant
- UV Protection:** Excellent; Meets EN13758-1
- Chemicals:** Excellent; resistant to water and petroleum
- Wicking:** Excellent; sheds surface moisture
- Welding Sparks / Spall:** Excellent



SRM Part Number	Bundle Outside Diameter		Bundle Circumference		Bundle Flat Width	
	In.	Mm.	In.	Mm.	In.	Mm.
RW-1.75RXX	1.75	44.45	5.50	139	6.25	158
RW-2.00RXX	2.00	50.80	6.20	157	7.75	196
RW-2.38RXX	2.38	60.45	7.48	190	8.90	226
RW-2.50RXX	2.50	63.50	7.80	198	9.30	236
RW-2.75RXX	2.75	69.85	8.64	219	10.15	257
RW-3.00RXX	3.00	76.20	9.40	239	11.00	279
RW-3.25RXX	3.25	82.55	10.20	259	11.70	297
RW-3.50RXX	3.50	88.90	11.00	279	12.50	317
RW-4.00RXX	4.00	101.60	12.50	317	14.00	355
RW-4.50RXX	4.50	114.30	14.00	355	15.50	393
RW-5.00RXX	5.99	127.00	15.75	400	17.25	438
RW-6.00RXX*	6.00	152.40	18.80	477	20.38	517
RW-7.00RXX	7.00	177.80	22.00	558	23.58	598
RW-8.00RXX	8.00	203.20	25.13	638	26.62	676
RW-9.00RXX	9.00	228.60	28.27	718	29.77	756
RW-9.50RXX	9.50	241.30	29.84	758	31.35	796
RW-10.00RXX	10.00	254.00	31.41	798	32.92	836
RW-11.00RXX	11.00	279.40	34.55	875	36.06	915
RW-12.00RXX	12.00	304.80	37.70	957	39.00	990
RW-13.00RXX	13.00	330.20	40.84	1037	42.35	1075
RW-13.50RXX	13.50	342.90	42.40	1077	43.91	1115
RW-14.50RXX	14.50	368.30	45.54	1156	47.05	1196
RW-15.00RXX	15.00	381.00	47.12	1197	48.62	1235
RW-16.00RXX	16.00	406.40	50.26	1276	51.76	1315

* Stock Size: RW-6.00RXX All other sizes are Made to Order and require a Minimum order of One (1) 75 Ft. / 22.86 Meter roll per size

Manufactured in the USA for SRM Industries Inc.