



# SRM INDUSTRIES INC.



The Toughest Hose Protection Products on the Planet...Period!

## RHINO SPIRAL GUARD™ HD

FRAS = FIRE RESISTANT ANTI STATIC

FR = FIRE RETARDANT



SRM FRAS P/N	SRM FR P/N	Hose O.D.		Range Opening in	
		In.	Mm.	In.	Mm.
RSG-38HDFRAS	RSG-38HDFR	0.38	10	0.39 - .66	10 - 27
RSG-50HDFRAS	RSG-50HDFR	0.50	11.5	0.47 - .86	12 - 22
RSG-62HDFRAS	RSG-62HDFR	0.62	14	0.62 - 1.06	16 - 27
RSG-95HDFRAS	RSG-95HDFR	0.875	20	0.86 - 1.37	22 - 35
RSG-1.125HDFRAS	RSG-1.125HDFR	1.00	25	1.06 - 1.69	27 - 43
RSG-1.50HDFRAS	RSG-1.50HDFR	1.50	32	1.30 - 2.17	33 - 55
RSG-1.75HDFRAS	RSG-1.75HDFR	1.75	38	1.65 - 2.52	42 - 64
RSG-2.25HDFRAS	RSG-2.25HDFR	2.00	50	2.05 - 2.95	52 - 75
RSG-2.62HDFRAS	RSG-2.62HDFR	2.63	60	2.56 - 3.80	65 - 96
RSG-3.00HDFRAS	RSG-3.00HDFR	3.00	72	3.15 - 4.30	80 - 110
RSG-4.00HDFRAS	RSG-4.00HDFR	4.00	87	3.80 - 4.90	97 - 125

AVAILABLE ONLY IN BLACK

Rhino Spiral Guard FRAS is MSHA Approved and is:

- Flame retardant and has an extremely good balance of mechanical properties
- Designed to allow you to wrap and bundle one or more hoses and or cables together at a time
- Has a conductive thermoplastic compound on a polypropylene base
- Anti Static - Conductivity is achieved by using a special conductive carbon black, in addition to low electrical resistancy
- Is manufactured to prevent the build up of a charge and discharging sparks in unstable environments that can cause fires
- Tested to: AS2600, AS1180.10B, and AS1180.13A



Rhino Spiral Guard FR is MSHA Approved and is:

- Flame retardant and has an extremely good balance of mechanical properties
- Designed to allow you to wrap and bundle one or more hoses and or cables together
- Designed so that it won't ignite in the event of a fire
- Tested to AS2600, AS1180.10B, AS1180.13A
- Can be used in any application that does not require a product to not ignite in the event of a fire

