



SRM INDUSTRIES INC.



The Toughest Hose Protection Products on the Planet...Period!

RHINO SPIRAL GUARD™ LIGHT DUTY

MATERIAL

Made with virgin low density polyethylene
Color: Black

PACKAGING

Available in 100 feet boxes

FEATURES

- **RHINO SPIRAL GUARD LIGHT DUTY** is designed to wrap around bundles to make neat looms and protect the conductors
- **RHINO SPIRAL GUARD LIGHT DUTY** will accommodate a large range of diameters and allows break outs at any point
- Meets California Prop 65
- Meets RoHS



SRM P/N:	Internal Dimensions		External Dimensions		Wall Thickness	
	ID in.	ID Mm.	OD in.	OD Mm.	In.	Mm.
RSG-38LD	0.40	11	0.50	12.70	0.04	1.02
RSG-50LD	0.55	14	0.63	16.02	0.04	1.02
RSG-62LD	0.69	17	0.79	20.07	0.05	1.27
RSG-95LD	0.95	24	1.00	25.40	0.07	1.78

Standard Box size: 100 feet



Manufactured in the USA for SRM Industries Inc.

Note: We reserve the right to make any engineering or material changes at any time to our products for enhancement, performance and quality.

Proper use of product is the sole responsibility of the user.



SRM INDUSTRIES INC.



The Toughest Hose Protection Products on the Planet...Period!

RHINO SPIRAL GUARD™ HD

Meets CA Prop 65
↓ Meets RoHS ↓

CROSS REFERENCE CHART

Meets CA Prop 65
Meets RoHS ↓

SRM P/N:	ID	Opening Range in Inches	Available Lengths in Feet	Aeroquip P/N:	I.D.	Dixon P/N:	I.D.	F & R P/N:	I.D.	Gates Global P/N:	Gates P/N:	I.D.	SRM P/N:
RSG-28HD	0.28	.28-.51	495	900952-4	0.24								RSG-28HD
RSG-38HD	0.38	.38-.66	165	900952-6	0.37					G80901-0006	7277-1174	0.38	RSG-38HD
RSG-50HD	0.50	.47-.86	66/100	900952-8	0.49	NFSGX16	0.45	93050	0.50	G80901-0008	7277-1175	0.50	RSG-50HD
RSG-62HD	0.63	.62-1.06	66/100	900952-10	0.63	NFSGX20	0.55	93063	0.63	G80901-0012	7277-1176	0.63	RSG-62HD
RSG-95HD	0.75	.86-1.37	66/100	900952-12	0.83	NFSGX25	0.80	93075	0.75	G80901-0016	7277-1177	0.84	RSG-95HD
RSG-1.125HD	1.13	1.06-1.69	66/100	900952-27	1.06	NFSGX32	1.00	93100	1.00	G80901-0020	7277-1178	1.06	RSG-1.125HD
RSG-1.50HD	1.50	1.30-2.17	66/100	900952-22	1.34	NFSGX40	1.25	93125	1.25	G80901-0024	7277-1179	1.34	RSG-1.50HD
RSG-1.50HD	1.50	1.30-2.17	66/100	900952-30	1.58	NFSGX50	1.50	93150	1.50				RSG-1.50HD
RSG-1.75HD	1.75	1.65-2.52	66/100			NFSGX63	2.00	93200	2.00	G80901-0028	7277-1180	1.73	RSG-1.75HD
RSG-2.25HD	2.25	2.05-2.95	66			NFSGX75	2.40	93250	2.50	G80901-0036	7277-1181	2.17	RSG-2.25HD
RSG-2.62HD	2.63	2.56-3.80	66			NFSGX90	2.83	93300	3.00	G80901-0044	7277-1182	2.60	RSG-2.62HD
RSG-3.00HD	3.00	3.15-4.30	66			NFSGX110	3.43	93350	3.50	G80901-0048	7277-1183	3.10	RSG-3.00HD
RSG-4.00HD	3.90	3.80-4.90	40					93400	4.00	G80901-0056	7277-1184	3.90	RSG-4.00HD
RSG-4.50HD	4.50	4.50-5.50	40							G80901-0072	7277-0001	4.33	RSG-4.50HD
RSG-5.00HD	5.00	4.80-6.00	27					93500	5.00				RSG-5.00HD
RSG-6.00HD	6.00	5.70-7.00+	20					93600	6.00				RSG-6.00HD

Meets CA Prop 65
↓ Meets RoHS ↓

Meets CA Prop 65
Meets RoHS ↓

SRM P/N:	ID	Opening Range in Inches	Available Lengths in Feet	Parker P/N:	ID.	Caplugs/Pigstail P/N:	I.D.	Safeplast P/N:	I.D.	Tompkins ProWrap Plus Extreme Duty P/N:	ID	Weather Head P/N:	I.D.	SRM P/N:
RSG-28HD	0.28	.28-.51	495			R95SSG	0.28							RSG-28HD
RSG-38HD	0.38	.38-.66	165			R12SSG	0.40	012C100Bk	.4	PWP-12	0.375			RSG-38HD
RSG-50HD	0.50	.47-.86	66/100			R16SSG	0.45	016C100Bk	.5	PWP-16	0.500	A9900	0.492	RSG-50HD
RSG-62HD	0.63	.62-1.06	66/100	HG-075	0.75	R20SSG	0.55	020C100Bk	.65	PWP-20	0.625	A9901	0.668	RSG-62HD
RSG-95HD	0.75	.86-1.37	66/100	HG-100	1.00	R25SSG	0.80	025C100Bk	.8	PWP-25	0.830			RSG-95HD
RSG-1.125HD	1.13	1.06-1.69	66/100	HG-125	1.25	R32SSG	1.00	032C100Bk	1.1	PWP-32	1.060	A9902	1.014	RSG-1.125HD
RSG-1.50HD	1.50	1.30-2.17	66/100	HG-150	1.50	R40SSG	1.26	040C100Bk	1.4	PWP-40	1.340	A9903	1.600	RSG-1.50HD
RSG-1.75HD	1.75	1.65-2.52	66/100	HG-200	2.00	R50SSG	1.50	050C100Bk	1.7	PWP-50	1.730			RSG-1.75HD
RSG-2.25HD	2.25	2.05-2.95	66			R63SSG	2.00	063C100Bk	2.2	PWP-63	2.170			RSG-2.25HD
RSG-2.62HD	2.63	2.56-3.80	66			R75SSG	2.40	075C75Bk	2.6	PWP-75	2.600	A9904	2.457	RSG-2.62HD
RSG-3.00HD	3.00	3.15-4.30	66	HG-350	3.50	R90SSG	2.83	090C50Bk	3.2	PWP-90	3.110	A9905	3.065	RSG-3.00HD
RSG-4.00HD	3.90	3.80-4.90	40			R110SSG	3.43	110C50Bk	3.9	PWP-110	3.900			RSG-4.00HD
RSG-4.50HD	4.50	4.50-5.50	40					235C40Bk	4.5					RSG-4.50HD
RSG-5.00HD	5.00	4.80-6.00	27			R140SSG	5.07	125C40Bk	4.5	PWP-140	5.070			RSG-5.00HD
RSG-6.00HD	6.00	5.70-7.00+	20			R160SSG	5.87	140C30Bk	5.0	PWP-160	6.000			RSG-6.00HD